



CAMOUFLAGE PAINT -- BULK

PRODUCT DATA SHEET

Description

Parker Camouflage paint is designed as a durable, high quality finish. For use on skiffs, canoes, boats or any surface requiring a flat camouflage finish. Parker Camouflage paint provides excellent water resistance, weathering, dries quickly to a dull finish that resists scratching and burnishing. Parker Camouflage paint applies easily to most any surface by brush, roller or spray*. Parker camouflage paint comes in five natural colors.

FINISH:	Flat
SUGGESTED DFT:	4-8 mils
VOLUME SOLIDS:	46%
FLASH POINT:	104° F. (40° C.)
THEORETICAL COVERAGE	738 square feet per gallon per dry mil
DRYING TIME:	<u>To touch:</u> 4-8 hours @ 75° F., 50% R.H., <u>Re-coat:</u> 12-24 hours @ 75° F., 50% R.H.
RECOMMENDED THINNER:	Paint Thinner or Mineral Spirits
SURFACE PREPARATION:	All surfaces should be clean, dry and free of all dirt, grease, oil, loose paint, rust and other foreign material. Glossy surfaces should be sanded or de-glossed.
MAX. SERV. TEMPERATURE:	200° F. (93° C.)
RESISTANCE:	<u>Water</u> – Very Good (not for constant immersion service) <u>Wearing</u> – Very Good
COMPATIBILITY:	Self priming on wood. Prime aluminum, steel, or fiberglass with a universal primer (Example: Parker 300 Primer).
APPLICATION:	Apply by brush, roller or spray. *Please note that flat film finishes settle or separate faster than conventional coatings. Mix contents thoroughly before use and stir periodically during application. Airless or HVLP spray: Airless spray: Use a fluid tip with .015” to .017” orifice is suggested at 2500 psi. HVLP: Use .051” fluid nozzle, #10 Air Cap.
COLOR:	Autumn Gold, Cattail Brown, Dead Grass, Moss Green, Sand Tan All Parker Camouflage paint colors come pre-packaged in 12 oz. spray cans for your convenience.

All technical advice, recommendations and services are rendered by the Seller gratis. They are based on technical data which the Seller believes to be reliable and are intended for use by persons having skill and know-how, at their own discretion and risk. Seller assumes no responsibility for results obtained or damages incurred from their use by Buyer in whole or in part. Such recommendations, technical advice or services are not to be taken as a license to operate under or intended to suggest infringement of any existing patent.

PARKER COATINGS, INC., P. O. BOX 10886, GREEN BAY, WI 54307-0886 – 1-920-494-9676 – 1-800-236-9676
www.parkercoatings.com